



SAFETY DATA SHEET

HIGH GLOSS concrete sealer

Issued: JAN 2025

NON-HAZARDOUS according to criteria of Safe Work Australia

1 PRODUCT & COMPANY UNDERTAKING IDENTIFICATION

Product Name: **HIGH GLOSS NATURAL LOOK concrete sealer**
Major Recommended Use: Concrete and masonry surface treatment. Industrial protective sealer.
Company: I-Chem Pty Ltd
ABN: 71 150 650 785
Address: 10 Yale Drive, Epping, Victoria, 3076
Telephone Number: +61 (0)410 542 100
Email: info@ichem.com.au

2 HAZARDS IDENTIFICATION

GHS Classification: Product as supplied is NON-HAZARDOUS according to criteria of Safe Work Australia

Signal word: Not applicable

Hazard statements: None applicable

Precautionary statements

Prevention
P273 Avoid release to the environment
P280 Wear protective gloves and eye/face protection

Response
P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+352 IF ON SKIN: Wash with soap and water
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

Storage
P403+235 Store in a well-ventilated place. Keep cool.

Disposal
P501 Dispose of contents/ container to an approved waste disposal plant.

Risk Statements: R36 Irritating to eyes.

Safety Statements: S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this SDS, container or label.

Hazard Category: Non-Hazardous according to criteria of Safe Work Australia

SUSDP: Not Scheduled as a Poison

ADG CLASS: Not classified as dangerous according to the Australian Dangerous Goods Code

Signs and Symptoms of Exposure (*Acute effects*):

Swallowed: Irritant. Can cause nausea, vomiting and stomach pain

Eye: Contact with eyes can cause mild irritation and discomfort, and may cause conjunctivitis and corneal oedema when absorbed into the tissue of the eye from the atmosphere. Corneal oedema may give rise to a perception of blue haze or fog around lights. This effect is transient and has no known residual effect.

Skin: Possible irritant to skin. Absorption through skin may occur. Prolonged and repeated contact may result in skin sensitization and dermatitis.

Inhaled: Inhalation risk unlikely in normal use. May cause, on prolonged inhalation, respiratory irritation, dizziness and nausea.

Chronic: Repeated and/or prolonged exposures may result in: adverse skin effects (de-fatting, rash or allergic reaction/sensitization), adverse eye effects (conjunctivitis).

3 COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS Number | Proportion | Hazard, Risk |
|---|-------------|------------|---------------|
| Acrylate Polymer dispersion | Proprietary | 10–30% | Xi; R36 |
| Triethanolamine | 102-71-6 | < 2% | Xi; R37/38 |
| Water | 7732-18-5 | > 60% | |
| Other ingredients below reportable concentrations | | 1–10% | Non-hazardous |

Description Non-hazardous waterborne acrylate polymer dispersion

4 FIRST AID MEASURES

- Swallowed:** If swallowed, do NOT induce vomiting, Give a glass of water and contact a doctor or Poisons Information Centre. Telephone **13 11 26**.
- Eye:** Immediately hold eye open and irrigate with water for 15 minutes. If persistent irritation occurs, obtain medical attention and see a Doctor.
- Skin:** Remove any contaminated clothing and product. Wash skin thoroughly with mild soap/water. Seek medical advice if ill effect or irritation develops.
- Inhaled:** Not considered applicable, however, if any effects are perceived, move patient to fresh air.
- First Aid Facilities:** Eyewash fountains and safety showers should be available for emergency use.
- Advice to Doctor:** Treat symptomatically. Dermatitis may result from prolonged or repeated exposure. Aspiration into the lungs may cause chemical pneumonitis.

5 FIRE FIGHTING MEASURES

- Suitable Extinguishing Media:** Presents no known fire or explosive hazards and forms no known hazardous decomposition products. Treat fire for materials actually involved in the fire.
- Special Exposure Hazards (fire fighting):** May generate toxic, irritating or flammable combustion products. Sudden reaction with fire may result if product is mixed with an oxidizing agent. May generate carbon monoxide gas. Personnel in vicinity and downwind should be evacuated.
- Special Fire Fighting Procedures:** Fire fighters should wear butyl rubber boots, gloves, and body suit and a self-contained breathing apparatus. Water spray should be used to cool intact drums. Prevent runoff from fire control entering waterways.
- HAZCHEM code:** Not applicable

6 ACCIDENTAL RELEASE MEASURES

- Precautions:** No special precautions. Wear protective clothing, boots, gloves, and eye protection.
- Methods for Cleaning Up:** If recovery is not feasible, admix with dry soil, sand or non-reactive absorbent and place in an appropriate chemical waste container. Transfer to containers by suction, preparatory for later disposal. Flush area with water spray. Clean up personnel must be equipped with non-absorbent/water repellent protective clothing, boots, gloves, and eye protection.
- For large spills, recover spilled material with vacuum truck then clean-up as above.

7 HANDLING & STORAGE

- Handling:** Avoid eye contact and repeated or prolonged skin contact.
- Storage:** Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Keep containers closed when not in use – check regularly for leaks.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Exposure Standards: | Triethanolamine | TWA (8 hours) | 2 ppm | TWA (8 hours) | 5 mg/m ³ |
|---------------------|-----------------|---------------|-------|---------------|---------------------|
| | | STEL (15 min) | - | STEL (15 min) | - |

Can be absorbed through the skin

- Engineering Controls:** Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.
- Hand Protection:** Wear impervious gloves if contact with liquid is possible. Viton offers good resistance; other materials may be less suitable. Check with equipment supplier to determine if level of protection is adequate.

| | |
|-------------------------|--|
| Eye Protection: | Splash proof eye goggles. |
| Body Protection: | Standard issue work clothes safety shoes or boots - chemical resistant. If splashes are likely to occur, wear: long sleeve overall. Check with equipment supplier to determine if level of protection is adequate. |
| Flammability: | Non-flammable |

9 PHYSICAL & CHEMICAL PROPERTIES

| | |
|--|---|
| Appearance: | Low viscosity, white milky liquid |
| Smell: | Mild acrylic odour |
| pH | 8.0 – 9.0 |
| Boiling Point (at 760 mmHg): | No data ($\approx 100^{\circ}\text{C}$) |
| Melting Point: | No data ($\approx 0^{\circ}\text{C}$) |
| Flashpoint: | Not applicable |
| Flammability: | Non-flammable |
| Explosive Limits: | Not applicable |
| Auto-ignition Temperature: | Not applicable |
| Oxidizing Properties: | No data |
| Vapour Pressure (20°C): | 2.27 kPa |
| Vapour Density (Air =1): | < 1 |
| Evaporation Rate (relative to nBA = 1.0) | No data |
| Solubility in Water: | Insoluble – disperses in water |
| Specific Gravity: | 1.00 – 1.04 |
| VOC content: | < 50 g/L < 5% by weight |

10 STABILITY & REACTIVITY

| | |
|--|---|
| Stability: | Stable under normal use conditions. May react with oxidizing agents. |
| Conditions to Avoid: | No data. |
| Incompatibility (Materials to Avoid): | Oxidizing agents, sodium or calcium hypochlorite. Reaction with peroxides may result in violent decomposition. |
| Hazardous Decomposition Products: | Carbon Monoxide, Carbon Dioxide in a fire. Irritating and toxic fumes at elevated temperatures. |
| Hazardous Transformation Products: | Will not occur. |

11 TOXICOLOGICAL INFORMATION

No product toxicological information is available:

| | |
|---|---------|
| Acute Oral Toxicity (LD₅₀): | no data |
| Acute Dermal Toxicity (LD₅₀): | no data |
| Acute Inhalation Toxicity (LC₅₀): | no data |

12 ECOLOGICAL INFORMATION

Basis for assessment: Ecotoxicological data have not been determined specifically for this product.

| | |
|-----------------------------------|---|
| Mobility: | No data available |
| Persistence/degradability: | No data available |
| Bioaccumulation: | No data available |
| Other adverse effects: | Product can be considered an environmental hazard through improper handling and improper disposal. Otherwise, no known significant effects or critical hazards. |

13 DISPOSAL CONSIDERATIONS

| | |
|----------------------------|---|
| Precautions: | Refer to Section 7 before handling the product or containers. |
| Waste disposal: | Recover or recycle if possible. Otherwise: Incineration. |
| Product disposal: | Recover or recycle if possible. Otherwise: Incineration. |
| Container disposal: | Drain container thoroughly and allow to dry. Empty container may be recycled. |
| Local legislation: | The recommendations given are considered appropriate for safe disposal. However, local regulations may be more stringent and these must be complied with. |

14 TRANSPORT INFORMATION

Not classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

| Mode | Regulations | Class | Packaging Group | Notes |
|-----------|-------------|----------------|-----------------|---|
| - | UN | None allocated | Not applicable | |
| Sea | IMDG | None allocated | Not applicable | This material is not classified as dangerous under IMDG regulations |
| Road/Rail | ADG Code | None allocated | Not applicable | This material is not classified as dangerous according to the Australian Dangerous Goods Code |
| Air | IATA/ICAO | None allocated | Not applicable | This material is not classified as dangerous under IATA regulations |

15 REGULATORY INFORMATION

EEC Symbol: C Corrosive
Xi Irritant

GHS Classification Product as supplied is NON-HAZARDOUS according to criteria of Safe Work Australia

Full text of H-Statements referred to under sections 2 and 3.

None applicable

EEC Council Directives relating to the classification, packaging and labelling of dangerous substances and preparations Risk (R) and Safety (S) phrases:

- R34: Causes burns.
- R36: Irritating to eyes.
- R37/38: Irritating to respiratory system and skin.
- R41: Risk of serious damage to eyes.
- R50: Very toxic to aquatic organisms.
- S23: Do not breathe vapour/mist/aerosol.
- S24/25: Avoid contact with skin and eyes.
- S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
- S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible)
- S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this SDS, container or label.

16 OTHER INFORMATION

Uses and restrictions: This product is designed and intended for use as a sealer for concrete and masonry.

SDS distribution: The information in this document should be made available to all who may handle the product.

Reference: The content and format of this safety data sheet is in accordance with the 3rd Revised Edition of the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia's Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals (2011)

Issue Date: 10th May, 2019

Reason for Issue: Minor formula change and change of contact details. Previous issue dated 19th May, 2017

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material